



NOTES:

1. The ramp shall have a 12-inch border with 1/4-inch grooves approximately 3/4-inch on center at the level surface of the sidewalk. The finish surface of the ramp including flared sides shall be firm, slip-resistant, and shall be of contrasting finish from that of the adjacent sidewalk.

NOT TO SCALE

CITY OF MILPITAS, ENGINEERING DIVISION

STANDARD DRAWING
NO. 420

REVISION
1

DATE

DESIGNED:

DRAWN: JV

CHECKED: MK

**CURB RAMP - INDUSTRIAL
SIDEWALK ADJACENT TO CURB**

ORIGINAL: 9/04/96
DATE

1

APPROVED BY:

PUBLIC WORKS DIRECTOR / CITY ENGINEER DATE: 11/9/00

SHEET 1 OF 2

CITY OF MILPITAS, ENGINEERING DIVISION				STANDARD DRAWING
REVISION	DATE	DESIGNED:	CURB RAMP - INDUSTRIAL SIDEWALK SEPARATED FROM CURB	NO. 420
1		DRAWN: JV		ORIGINAL: 9/04/96 DATE
		CHECKED: MK		
		1	APPROVED BY: <i>Daniel M. McNeely</i> PUBLIC WORKS DIRECTOR / CITY ENGINEER	SHEET 2 OF 2
			DATE: 11/9/00	